

# JA-68

JA-68

JA-80 OASiS, JA-63 Profi Jablotron  
JA-65 Maestro.

ON). (DIP

DIP

JA-68

4  
RJ-44

CT-04.

10



1

JP1  
NO).

NC (

( ARM LB)

|            |             |
|------------|-------------|
|            | ( ARM LB: ) |
| <b>+U</b>  | 200 )       |
| <b>GND</b> |             |
| <b>C</b>   | ( )         |
| <b>ARM</b> | (A B ABC)   |
| <b>ALM</b> |             |
| <b>FIR</b> |             |
| <b>TMP</b> |             |
| <b>PNC</b> |             |
| <b>FLT</b> | ( )         |
| <b>AC</b>  |             |
| <b>LB</b>  | ( )         |

1

DIP.

10

JA-68

ON

2, 3, 4 5

DIP

|    |            |     |
|----|------------|-----|
|    |            |     |
| 1  | <b>ARM</b> | -   |
| 2  | <b>ALM</b> |     |
| 3  | <b>FIR</b> |     |
| 4  | <b>TMP</b> |     |
| 5  | <b>PNC</b> |     |
| 6  | <b>FLT</b> |     |
| 7  | <b>AC</b>  |     |
| 8  | <b>LB</b>  |     |
| 9  | <b>PGX</b> | PGX |
| 10 | <b>PGY</b> | PGY |

2

|           |  |
|-----------|--|
|           |  |
| <b>NC</b> |  |
| <b>C</b>  |  |
| <b>NO</b> |  |

3

10

8 + 1

10

12 ( )

8

+ 1

200  
1 A / 60

10

2x RJ-44

CT-04

10

10

-10 +40 °C

VO-R/10/08.2005-24

ETSI EN 300220, ETS 300683, EN 60950



Jablotron Ltd.

Directive 1999/5/EC.

JA-68

[www.jablotron.com](http://www.jablotron.com)



Jablotron Ltd., Pod Skalkou 33  
466 01 Jablonec nad Nisou  
Czech Republic  
Tel: +420 483 559 911  
fax: +420 483 559 993  
Internet: [www.jablotron.com](http://www.jablotron.com)

MGK23700\_PTS